



Why come to us for a solution?

- Quality products
- Wide range of products
- Nationwide backup
- Locally produced UPS's
- Competitively priced
- Unique design
- Good value for money
- 24 hours after sales services



eco SERIES

LINE-INTERACTIVE UPS 600VA - 2.2KVA

Economically designed, this unit is manufactured to have a small carbon footprint. The ECO series is an excellent option for small office or home environments where you want the best protection, at the right price. Being environmentally friendly and highly reliable makes the ECO Series UPS great value for money.



APPLICATION

Computers, Terminals, Servers, DeskJet Printers, Modems, PABX's, Diginet, Premicell, etc.

FEATURES

- Wide input voltage window
- Small carbon footprint
- Boost and buck AVR
- Compatible with generators
- Provide LED indication and audible alarm function
- Surge protection
- Protection for short circuit and battery low voltage
- Automatic diagnostic when start-up
- Automatic battery charge in UPS off mode
- USB communication with monitoring software
- Cold start function
- Intelligent battery management



MODEL	ECO 600	ECO 1000	ECO 1400	ECO 2200
CAPACITY	600VA/360W	1000VA/600W	1400VA/840W	2200VA/1320W
INPUT				
PHASE	single phase			
VOLTAGE RANGE	230V ±20%			
FREQUENCY	50Hz			
OUTPUT				
VOLTAGE	230V ±10%			
WAVEFORM	AC mode: sine wave; battery mode; step square sine wave			
FREQUENCY	50Hz			
TRANSFER TIME	typical 6ms			
PROTECTION				
SURGE PROTECTION	varistor			
SHORT CIRCUIT	fuse			
COMMUNICATION				
	USB			
BATTERY				
TYPE	sealed lead acid, maintenance free			
RECHARGE	after full discharge, charge to 8 hours to 90% capacity			
BACKUP TIME	10-15min load dependent			
CHARGE CURRENT	350mA ~ 1A			
BATTERY CONFIGURATION	1x 12V/7AH	2x 12V/7AH	4x 12V/4.5AH	
INDICATION				
AC MODE	yellow LED on, green LED on, red LED off, no beep			
CHARGING BATTERY	yellow LED on			
BATTERY MODE	red LED flash, buzzer beep every 5 seconds			
BATTERY LOW	red LED flash, buzzer beep twice per second			
OTHER				
AUDIBLE NOISE AT 1M	<45 dB			
TEMPERATURE	0~40°C			
HUMIDITY	95% (non-condensing)			
NET/GROSS WEIGHT	5.8 / 6.5 kg	10.9 / 11.6 kg	12.1 / 12.8 kg	19.5 / 22 kg
UNIT DIMENSIONS (W-D-H)	95 x 320 x 160 mm	124 x 378 x 223 mm		142 x 425 x 320 mm
PACKAGE DIMENSIONS (W-D-H)	147 x 376 x 246 mm	188 x 450 x 311 mm		272 x 565 x 350 mm

Notes: